



T-REX A MINERAL

PRODUCT DESCRIPTION:

T-REX A is a versatile multi-purpose transmission fluid specifically formulated for use in automatic gearboxes requiring GM Type A Suffix A specifications. Its advanced formula ensures exceptionally smooth operation of torque converters and fluid couplings in automatic transmissions. T-REX A provides reliable performance, enhancing the efficiency and longevity of the transmission system under various operating conditions.

APPLICATION:

T-REX A is suitable for use in automatic transmissions of passenger cars and light-duty trucks as well as in other power shift transmissions, industrial torque converters, power steering systems and manual transmissions, where a low-viscosity fluid of GM ATF TYPE A quality is specified.

FEATURES & BENEFITS:

- Excellent oxidation stability
- High viscosity index
- Corrosion prevention
- Smoothen transmission process
- Foaming resistance
- Controlled friction properties

MEETS OR EXCEEDS:

- GM Type A Suffix A

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	T-REX A
Grade			Type A
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	52
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	7.5
Viscosity Index	ASTM D2270	-	106
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	220
Pour Point (max)	ASTM D97	°C	-27

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internal reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internal.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.