



## T-REX CVT

### CONTINUOUSLY VARIABLE TRANSMISSIONS

#### PRODUCT DESCRIPTION:

T-REX CVT is a premium fully synthetic transmission fluid designed for a wide range of passenger cars and vans. This advanced fluid offers excellent metal-to-metal frictional properties, effectively reducing belt and chain slippage to enhance transmission durability. It delivers superior anti-shudder performance while minimizing noise, vibration, and harshness for a smoother driving experience.

#### APPLICATION:

Especially recommended for use in push belt and chain-driven continuously variable transmissions of most European, Asian, and American passenger cars and vans.

#### FEATURES & BENEFITS:

- Exceptional steel on steel friction durability maintains transmission performance
- Good gear wear protection prolongs the performance and life of the transmission
- High shear stability and enhanced anti foaming and air release characteristics maintain effective lubrication
- Superior wet-clutch performance for outstanding anti-shudder durability and reduced noise, vibration and harshness
- In elevated heat, guards against the harmful effects of thermal breakdown

#### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	T-REX CVT
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	7
Viscosity Index (min)	ASTM D2270	-	140
Density@15°C/ 60°F	ASTM D4052	g/cm <sup>3</sup>	TBR
Flash Point (min)	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42
Brookfield Viscosity @ -40 °C	ASTM D2983	°C	9000

#### MEETS OR EXCEEDS:

AUDI	G 052 180, G 052 516, Multitronic, TL 52 116, TL 52 180, TL 52 516
BMW	83 22 0 136 376, 83 22 0 429 154, EZL 799, EZL 799 A
CHERY	CVT
CHRYSLER	CVTF+4, NS-2
CITROËN	AMMIX CVTF DFE, AMMIX CVT Fluid DC, AMMIX CVT, Fluid DFE, CVTF 3320, CVT Fluid DFC, Fluid TC
DAIHATSU	1 490 761, 1 490 763, POWERSHIFT, WSS-M2C200-D2, WSS-M2C200-D3, WSS-M2C200-E1, WSS-M2C936-A
DODGE	05191184AA, CVTF+4, NS-2
DS (CAPSA)	9735 EF, Elfmatic CVT, Elfmatic CVT MV
FIAT	Tutela Car CVT N.G
FORD	CVT23, CVT30, MERCON C, WSS-M2C928-A, WSS- M2C933-A, XT-7QCFT
HONDA	1940713, 1940714, CVTF I-Green2, DEX-CVT, HP CVTF 95529854, VT40
HYUNDAI	CVT-1, Genuine CVTF, SP-CVT 1, SP III (CVT models only)
INFINITI	NS-1, NS-2, NS-3



JEEP	05191184AA, CVTF+4, NS-2, VTF
KIA	CVT-1, SP-CVT 1, SP III (CVT models only)
LEXUS	CVTF 3320, CVT FE, Fluid FE, Fluid TC
LIFAN	CVT
MAZDA	CVTF 3320, JWS 3320
MERCEDES-BENZ	A 001 989 46 03, MB 236.20
MG	EM-CVTF
MINI	83 22 0 136 376, 83 22 0 429 154, COOPER EZL 799 A, EZL 799, ZF CVT V1
MITSUBISHI	CVTF ECO J4, Dia Queen CVTF-J1 (MMC Diaqueen CVT Fluid J1), Dia Queen CVTF-J4, Dia Queen CVTF-J4+ (MMC Diaqueen CVT Fluid J4 and J4+), MZ313973, SP III (CVT models only)
NISSAN	999MP-NS200P, KTF-1, N-CVT, NS-1, NS-2, NS-2V, NS-3
OPEL	7-speed CVT, HP CVTF 95529854, VT40
PEUGEOT	9735 EF, Elfmatic CVT, Elfmatic CVT MV
RENAULT	CVT CK/SK/FK, Elfmatic CVT, Elfmatic CVT MV
ROVER	EM-CVTF, Unipart Transmatic ATF
SATURN	22688912, DEX-CVT
SEAT	G 052 180, G 052 516
SUBARU	CV30, CVT III Fluid, CVT TR580, CVT TR690, ECVT, High Torque CVT, High Torque CVTF-LV, iCVTF, i-CVTF FG, K0421Y0700, K0425Y0710, K0425Y0711, Linear-tronic chain CVT 3 Fluid, Lineartronic chain CVT and CVT II Fluid, Lineartronic CVTF, Lineartronic High Torque (HT) CVT Fluid, Lineartronic II, NS-2, SOA748V0300
SUZUKI	CVTF 3320, CVTF FE, TC
TOYOTA	7-speed CVT, HP CVTF 95529854, VT40
VAUXHALL	CVTF 4959
VOLVO	G 052 180, G 052 516
VW	RDCF01, RDCF02, CVTs
ZOTYE	22688912, DEX-CVT

**DISCLAIMER:** The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internal reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

#### HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at [www.internal.net](http://www.internal.net).

#### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.