



T-REX II MINERAL

PRODUCT DESCRIPTION:

T-REX II is a high-quality automatic transmission fluid formulated with highly refined base stocks and advanced additive technology. Designed for use in passenger cars and light commercial vehicles, it effectively reduces transmission "chatter," ensuring smooth and quiet operation across all speeds and conditions. T-REX II provides optimal oxidation and thermal stability, excellent friction control, superior cleanliness, high load-carrying capacity, and robust wear and corrosion protection. This fluid ensures extended transmission life and reliable performance under a wide range of operating conditions.

APPLICATION:

Suitable for automatic gearboxes of passenger cars, power steering, vans, truck and buses where the manufacturer recommends an ATF GM Dexron II D.

FEATURES & BENEFITS:

- Very high viscosity index linked with an excellent viscosity stability in operation
- Very low pour point
- Very good thermal stability
- Excellent resistance to oxidation
- Friction properties specific to the requirements.

MEETS OR EXCEEDS:

- GM DEXRON IID
- CHRYSLER +3
- VOITH H55.6335
- VOLVO 97355
- FORD ESP-M2C138-CJ / ESP-M2C166-H
- ALLISON TES 389, ALLISON TES 228(C4)
- MB 236.1/236.5/236.7
- ZF TE-ML-04D / 09 / 11A / 14A
- BMW 81 22 9 400 272/81 22 9 400 275/81 22 9 407 738
- CAT TO-2
- TOYOTA TII/2
- MAN 339 TYPE L2/V1
- OPEL 19 40 700 / 19 40 707
- MITSUBISHI SP / SP2/ BTR

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	T-REX II
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C, min	ASTM D7042	cSvt	7.1
Viscosity Index	ASTM D2270	-	140
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internal reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internal.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.