



T-REX VI

SYNTHETIC

PRODUCT DESCRIPTION:

T-REX VI is a fully synthetic automatic transmission fluid designed to meet the requirements of passenger cars and light trucks requiring GM Dexron VI or earlier generation fluids. This high-performance fluid is compatible with various Aisin Warner transmission models, including AW TF-80SC/SD, AWF21, AF40-6, AM6, AW6A-EI, TF81SC, AF21, and GA6F21WA (Mini). T-REX VI ensures superior performance, durability, and efficiency in automatic transmissions, providing excellent protection and smooth operation under diverse driving conditions.

APPLICATION:

All automatic transmissions that require a GM Dexron VI or earlier generation transmission fluid. Hydraulic systems or industrial and mobile equipment operating over a wide temperature range.

FEATURES & BENEFITS:

- Meets stricter performance requirements for new GM 6 Speed automatic transmissions.
- Outstanding friction durability for consistent shift performance for the life of the fluid.
- Excellent oxidation resistance and thermal stability for long fluid life.
- Protects against sludge and varnish formation.
- Protects against wear.
- Protects against rust and corrosion
- High shear stability
- Excellent low temperature properties.
- Good seal compatibility
- Foam resistance

MEETS OR EXCEEDS:

- JWS 3309, JWS 3324, T-IV, AW-1, NWS 9638
- AS 68RC (T IV)
- AUDI/VW G-052-162-A1/A2
- BMW ETL-7045, 7045E, LA2634, ETL-8072B, 81 22 9 400 275
- CHRYSLER M1375.4
- FIAT (ALL VEHICLES) TYPO T-IV
- GENERAL MOTORS DEXRON II/III/IIII/VI
- HONDA ACURA Z-1 PREMIUM, HONDAMATIC S
- HYUNDAI / KIA SP IV, HYUNDAI SPH-IV
- ISUZU BESCO ATF II, ATF III
- JAGUAR ATF 3403 M115, JLM 20238
- LT 71141
- MAZDA ATF M III
- MERCON LV
- MITSUBISHI DIAMOND SP-IV
- MB ZF 4 HP20, 236.1/5/6/7/8/9/236.41
- PEUGEOT ZF 4 HP20
- PORSCHE ATF 3403-M115
- SUBARU ATF, ATF HP
- TOYOTA TYPE T-III, T-IV
- TOYOTA WS
- VOLVO T-IV
- VOITH 55.6635 / VOLVO 97340
- ZF 5HP 18FL/19FL/24A
- ZF 5HP 30
- ZFF TE-ML 09
- BMW P/N 833227542290
- CITROEN P/N PR 9980
- SAAB P/N 93165147
- TOYOTA P/N 08886-02305/08886-81015

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	T-REX VI
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	6.0
Viscosity Index (min)	ASTM D2270	-	140
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42
Viscosity Brookfield @ -40 °C	ASTM-2983	mPa.s (cP)	12500

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internol reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internol.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.