



TORQON MULTI HF

Multifunction Hydraulic Fluid

PRODUCT DESCRIPTION:

TORQON MULTI HF is a high-performance synthetic-based multifunctional hydraulic fluid specifically designed for modern vehicles equipped with advanced hydraulic systems. This includes power steering, hydraulic dampers, suspensions, hard tops, and centralized hydraulic systems. Its superior formulation ensures optimal performance, excellent system protection, and smooth operation across a wide range of conditions.

APPLICATION: This product is particularly recommended to be used with the following European OEM's: VW (VAG), AUDI, PORSCHE, BMW, CITROËN, MERCEDES, MINI, PEUGEOT, VOLVO, SAAB and American: FORD, GENERAL MOTORS-OPEL.

FEATURES & BENEFITS:

- Protects hydraulic pumps heavily loaded.
- Extends life time duration of all systems.
- Provide comfort and noise reduction especially at cold conditions.
- Provide outstanding anti-wear, anti-corrosion and anti-foam properties.

PERFORMANCE MEET OR EXCEEDS:

DIN	51 524 T2, 51 524 T3
ISO	7308
AUDI	G 002 000, G 004 000, TL 52 146
BENTLEY	RH 5000, TH 5000
BMW	54 34 0 392 235, 54 34 0 394 395, 54 34 7 117 733, 81 22 9 407 758, 82 11 0 148 132, 82 11 1 468 041, 83 29 0 429 576
CHRYSLER	05127381AB, 68088485AA, MS 10838, MS 11655, MS 5931
CITROËN	9730 A5, 9735-EJ, 9735-EJ, 99 7969, 9979-AI, 9979 A4, H 50126, PSA S71 2710, Total Fluide DA, Total Fluide LDS
DODGE	MS 11655
DS (CAPSA)	9730 A5, 99 7969, 9979 A4, H 50126, Total Fluide DA, Total Fluide LDS
FENDT	X 902 011 622
FIAT	9 55550-SA1, Tutela GI/R
FORD	WSS-M2C204-A
FUCHS	Rave ZH 3044, Rave ZH 4300 B
GENERAL MOTORS	B 040 0070, B 040 0070, B 040 2012, GM 1940715, GM 1940766
HYUNDAI	00232-19017, PSF-4
JEEP	MS 11655
KIA	00232-19017, PSF-4
LAND ROVER	Cold Climate PAS Fluid LRN2261, LRO03401
LEXUS	PSA S71 2710, PSF NEW-W
MAN	M 3289 (3623/93)
MERCEDES-BENZ	001 989 24 03 10, 001 989 24 03 12, MB 345 0, Q 132 0001
MINI	54 34 0 392 235, 54 34 0 394 395, 54 34 7 117 733, 81 22 9 407 758, 82 11 0 148 132, 82 11 1 468 041, 83 29 0 429 576
OPEL	B 040 0070, B 040 2012, GM 1940 715, GM 1940 766
PEUGEOT	9730 A5, 9735-EJ, 99 7969, 9979 A4, H 50126, PSA S71 2710, Total Fluide DA, Total Fluide LDS
PORSCHE	000 043 203 33, 000 043 206 56
SAAB	3032 380, 93160548
SEAT	G 002 000, G 004 000, G 004 012, TL 52 146
SKODA	G 002 000, G 004 000, G 004 012, TL 52 146
TOYOTA	PSA S71 2710, PSF NEW-W
VOLVO	1161529, 1273 36, 30741424
VW	G 002 000, G 004 000, G 004 012, TL 52 146, TL 52 146
ZF	TE-ML 02K

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	TORQON MULTI HF
Kinematic Viscosity @100C	D445	cSt	6.2
Kinematic Viscosity @40C	D445	cSt	19
Viscosity Index	D1120	-	320
Density@20C	D1298	g/cm3	TBR
Flash Point (min)	D92	°C	154

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internol reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internol.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.