



GLACIER DEXCOOL 50
EXTENDED LIFE COOLANT/ ANTIFREEZE

PRODUCT DESCRIPTION:

GLACIER Dexcool 50 is a single-phase, ethylene glycol-based extended-life coolant formulated for automotive engines. It is designed to deliver superior protection and performance while meeting GM 6277M, the General Motors specification for extended-life coolant. This ensures compatibility and reliability for vehicles requiring this standard.

APPLICATION:

GLACIER Dexcool 50 is recommended for diesel and gasoline applications requiring nitrite, silicate and phosphate free extended life coolant.

FEATURES & BENEFITS:

- Outstanding corrosion protection
- Contains no amines, nitrites or phosphates
- Universal application at passenger cars and commercial vehicles.
- Anti-cavitation, preventing foam and the retention of air, ensuring the good performance of the pump.
- Prevents the build-up of deposits, keeping the cooling system clean.
- Long life service product

PERFORMANCE MEET OR EXCEEDS:

- GM 6277M/1825M/1899M
- US FED A-A-870-A
- CHRYSLER MS 9769
- FORD WSS-M97B44-D2
- VAG G-12
- ASTM D4656

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	GLACIER DEXCOOL 50
pH	D1278	cSt	8.1
Freezing Point	D1177	°C	-37
Boiling Point	D1120	cSt	110
Density at 15.5C	D4052	g/cm3	TBR

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internal reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internal.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.