



GRIPTO-TECH LC 40-EP-SEMI SYN

PRODUCT DESCRIPTION:

GRIPTO-TECH LC 40-EP-SEMI SYN is a semi-synthetic fluid grease designed for use in centralized lubrication systems in trucks and buses. It is formulated with a blend of highly refined mineral and selected synthetic base oils, enhanced with extreme pressure and specialized additives. This combination ensures exceptional protection and performance under a wide range of operating conditions.

APPLICATIONS

This grease is suitable for centralized lubricating installations in utility vehicles as well as for outside working units having long lubrication feed lines. This product is semi-fluid and may also be used for many gear types, where grease lubrication is recommended. It is also used for lubrication of rail vehicle wheels, truck wheel bearings, roller bearings in crushers, mills and mixers general lubrication applications in steel plants, especially hot and cold rolling mills, centralized lubrication systems where grease is supplied to highly loaded lubrication points.

PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 140°C
- Effective extreme pressure properties
- Enhanced load-carrying and wear protection properties
- Good pumpability
- Good water washout properties

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	-	00/000
Thickener Type	-	Lithium-calcium
Appearance	Visual	Smooth & Homogenous
Color	Visual	Red
Base Oil Type	-	Semi Synthetic
Work Penetration @25°C	ASTM D217	440
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b
Dropping Point °C	ASTM D2265	N/A
Operating Temperature Range, °C	INTERNAL	-20 to 140
Base Oil Viscosity @40 °C (Cst)	ASTM D445	40.0
Base Oil Viscosity @100°C (Cst)	ASTM D445	7.0

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internal reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internal.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.