



MAXSHIFT ULTRA

EXTREME PRESSURE AUTOMOTIVE GEAR OIL

PRODUCT DESCRIPTION:

MAXSHIFT ULTRA is a premium extreme pressure (EP) gear lubricant formulated with high-quality base stocks, advanced sulfur-phosphorus additives, friction modifiers, and corrosion inhibitors. It meets API GL-5 standards and a variety of manufacturer specifications. Designed for automotive applications, it delivers exceptional thermal stability and extreme pressure performance, ensuring reliable protection and optimal gear performance across a wide range of temperatures and demanding conditions.

APPLICATION:

MAXSHIFT ULTRA oils are mainly recommended for use in spiral bevel and hypoid differentials, power dividers and transmissions requiring EP gear lubes under high speed, high load, high torque and high horse power conditions. MAXSHIFT ULTRA meets or exceeds the quality requirements of numerous vehicle manufacturers such as IVECO, MAN, SCANIA and VOLVO for heavy vehicles rear axles and final drive units.

FEATURES & BENEFITS:

- Extreme pressure properties protect hypoid and other types of gears from scuffing and wear.
- Superior thermal and oxidative stability.
- High safety margin against foaming and corrosion.
- Protects against oil seal deterioration.

MEET OR EXCEEDS:

SAE GRADES	90	140	80W-90	85W-90	80W-140	85W-140	75W-80	75W-90
API	GL-5	GL-5	GL-5	GL-5	GL-5	GL-5	GL-5	GL-5
MIL	MIL-L-2105D	MIL-L-2105D	MIL-L-2105D	MIL-L-2105D	MIL-L-2105D	MIL-L-2105D	MIL-L-2105D	MIL-L-2105D
MAN	342 M2	-	342 M2	342 M2	-	-	342 M2	342 M2
ZF	12E/16B 16C/17B 19B/21A	16D	12E/16B 16C/17B 19B/21A	12E/16B 16C/17B 19B/21A	12E/16C 16D/21A	12E/16C 16D/21A	12E/16B16C 17B/21A	12E/16B16C 17B/21A

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	MAXSHIFT ULTRA							
			90	140	80W-90	85W-90	80W-140	85W-140	75W-80	75W-90
KV@ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
KV@212°F /100°C	D7042	cSt	17.5	28.3	15.6	17.5	28.5	28.2	9.8	14.4
Viscosity Index (min)	D2270	-	95	95	140	140	140	140	140	140
Density@15°C	D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	200	200	200	200	200	200	200	200
Pour Point (max)	D97	°C	-9	-9	-27	-15	-27	-12	-42	-42
Brookfield Viscosity	D2983	cp	-	-	<150,000 (-26C)	<150,000 (-12C)	<150,000 (-12C)	<150,000 (-26C)	<150,000 (-40C)	<150,000 (-40C)

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internol reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internol.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.