



MOTOX 4T SYNTH HD 20W-50

SYNTHETIC

PRODUCT DESCRIPTION:

MOTOX 4T SYNTH HD 20W-50 is a fully synthetic motorcycle oil designed specifically for air- and water-cooled four-stroke engines, making it particularly ideal for Harley Davidson motorcycles. Its carefully selected base oils and premium additive components deliver optimal lubrication, superior engine cleanliness, and excellent friction performance under all operating conditions. This oil is perfectly suited for use with both wet and dry clutch systems.

APPLICATION:

MOTOX 4T SYNTH HD 20W-50 is intended for use in four-stroke engines of scooters, mopeds, motorcycles and ATVs, which require API SN performance level, and also for motorbikes' transmissions and clutches, which need lubrication by motor oils.

FEATURES & BENEFITS:

- Stable to ageing and stable viscosity
- Excellent wear resistance
- Outstanding corrosion protection
- High engine cleanliness
- Outstanding high temperature stability

MEETS OR EXCEEDS:

- API SN
- JASO MA2

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	MOTOX 4T SYNTH HD 20W-50
Grade			20W-50
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	19.5
Viscosity Index	D2270	-	120
TBN	D8698	mgKOH/g	7
Density@15°C/ 60°F	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	220
Pour Point (max)	D97	°C	-24

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internal reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internal.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.