



## MOTOX SHOCK ABSORBER OIL

### PRODUCT DESCRIPTION:

MOTOX SHOCK ABSORBER OIL is a high-performance oil crafted with premium synthetic base oils and advanced additives to deliver exceptional damping performance for motorcycle shock absorbers. It features excellent viscosity-temperature stability, outstanding oxidation resistance, and superior anti-foam properties. Additionally, it ensures excellent seal compatibility, contributing to optimal shock absorber performance and longevity.

### APPLICATION:

Recommended as hydraulic fluid for front fork motorcycles & other shock absorbers mechanism.

### FEATURES & BENEFITS:

- Increase the life of shock absorber
- Excellent seal compatibility
- Longer oil life
- Excellent damping effect
- Excellent low temperature properties

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	MOTOX SHOCK ABSORBER OIL
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	32
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	5.9
Viscosity Index	ASTM D2270		130
Flash Point (min)	ASTM D92	°C	210
Pour Point	ASTM D97	°C	-24

**DISCLAIMER:** The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internal reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at [www.internal.net](http://www.internal.net).

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.