



MOTOX SUPER SCOOTER

PRODUCT DESCRIPTION:

MOTOX SUPER SCOOTER is crafted using premium-quality base stocks combined with advanced additives and a stable thermal detergent system to enhance engine cleanliness and durability. This lubricating oil minimizes friction while providing superior protection for motorcycle engines. As a JASO MB-certified lubricant, it ensures optimal engine performance and improved fuel efficiency for all scooters without a wet clutch.

APPLICATION:

For scooters without wet clutch and where JASO MB specification is required.

FEATURES & BENEFITS:

- Contains Detergent Additive System with Thermal Stable to control deposit levels.
- Protects the engine from deposits optimally and the engine life increases longer.
- Has a high level of viscosity which makes the engine sound smoother.

MEETS OR EXCEEDS:

- API SL
- JASO MB

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	MOTOX SUPER SCOOTER	
			10W-30	10W-40
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F/40°C	ASTM D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F/100°C	ASTM D7042	cSt	11.90	14.0
Viscosity Index	ASTM D2270	-	145	145
SPGravity @15°C/60 °F	ASTM D4052	g/cm3	TBR	TBR
Flash Point	ASTM D92	°C	220	220
Pour Point	ASTM D97	°C	-36	-36
TBN	ASTM D2896	Mg KOH/g	7.0	7.0

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internal reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internal.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.