



**PULSE 4 LV**

**PRODUCT DESCRIPTION:**

PULSE 4 LV is an advanced high-specification brake and clutch fluid designed to meet the stringent requirements of ISO 4925 Class 6. Its exceptional low-temperature viscosity ensures optimal fluid circulation through micro-valves, enhancing the responsiveness of ABS, ESP, and ASR high-pressure systems. With a higher wet boiling point compared to conventional DOT 4 fluids, PULSE 4 LV provides extended product life and superior performance in demanding driving conditions.

**APPLICATION:**

PULSE 4 LV brake fluid can be used in all vehicles where ISO 4925 Class 6 specification is required. It is especially recommended for use in hydraulic brake and clutch systems of vehicles fitted with ABS (Anti-lock Braking System), ESP (Electronic Stability Program) and ASR (Acceleration Slip Regulation). PULSE 4 LV is mixable with DOT 3, DOT 4 and DOT 5.1 NON-SILICONE BASE products. Do not mix with silicone (DOT 5 silicone base) or mineral base fluids (LHM).

**FEATURES & BENEFITS**

- Optimal ABS properties.
- Exceptional chemical stability.
- High lubricating power.
- Exceptional low viscosity at low temperature.
- Higher Dry and Wet boiling points.
- Miscibility with all brake fluids of the same specification.

**TYPICAL PROPERTIES:**

PARAMETERS	PULSE 4 LV
ISO	4925 Class 6
FMVSS 116	DOT 4
SAE	J 1704
MB	331.0
VW	501.14 (TL 766-Z)
FORD	WSS-M6C65-A2/M6C57-A2
BMW	QV 34001

**DISCLAIMER:** The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internal reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

**HEALTH & SAFETY, ENVIRONMENT:**

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at [www.internal.net](http://www.internal.net).

**PROTECT THE ENVIRONMENT:**

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.