

MATERIAL SAFETY DATA SHEET

SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name:	INTERNOL GRIPTO-TECH LC 150-EP-M5-SYN NLGI 0
Product Code:	364
SDS No.:	INT364
Product Type:	Semi solid
1.2Relevant Identified	Uses of the Substance or Mixture and Uses Advised
Against	
Use of the Substance / Mixture:	GREASE For specific application advice see appropriate Technical Data Sheet or consult our company representative.

1.3Details of the Supplier of the Safety Data Sheet

Supplier:	REXOL FZC, PO Box 52341, Plot 1F-09B, 09B Hamriyah Free Zone, Sharjah, United Arab Emirates
Supplier Phone & Email Address:	Phone: +971 6 561 8895 Email: info@venomoil.de
Date of Issue	01-DEC-2021
Date of Revision	01-JAN-2025
Prepared by:	REXOL FZC

1.4Emergency Telephone Number

Emergency Telephone Number:	United Arab Emirates, Government of Sharjah, Hamriyah Free
	Zone Authority, SAFETY PH NO. +971 6 526 1666 (24x7)
	EMERGENCY PH NO. +971 6 526 2111 (24x7)



SECTION 2: Hazard Identification

2.1 Classification of the Substance / Mixture

Classification according to DirectiveThe product is not classified as dangerous according to Directive	
1999/45/EC [DPD]	1999/45/EC and its amendments.
	See sections 11 and 12 for more detailed information on health

effects and symptoms and environmental hazards.

2.2Label Elements

Signal Word:	No signal word.
Hazard Statements:	No known significant effects or critical hazards.
Precautionary Statements:	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Supplemental Label Elements:	Not applicable.
Special Packaging Requirements:	
Containers to be fitted	Not applicable.
with child-resistant	
fastenings	
Tactile Warning of Danger:	Not applicable.

2.3Other Hazards

Other Hazards which do not Resul	t Defatting to the skin.
in Classification:	USED GREASE
	Used grease may contain hazardous components, which have
	the potential to cause skin cancer.
	See Toxicological Information, section 11 of this Safety Data
	Sheet.

SECTION 3: Composition/Information on Ingredients



Substance / Mixture:

Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). This product does not contain any hazardous ingredients at or above regulated thresholds.

SECTION 4: First Aid Measures

4.1 Description of First Aid Measures

Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Eye Contact:	Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin Contact:	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Ingestion:	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if Symptoms occur.
Inhalation:	If inhaled, remove to fresh air. Get medical attention if symptoms appear. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Protection of First Aiders:	
	No action shall be taken involving any personal risk or without suitable training.

4.2Most Important Symptoms and Effects, Both Acute and Delayed

See Section 11 for more detailed information on health effects and symptoms.



4.3Indication of Immediate Medical Attention and Special Treatment Needed

Notes to Physician:See Section 11 for more detailed information on health effects
and symptoms.

SECTION 5: Fire Fighting Measures

5.1 Extinguishing Media

Suitable Extinguishing Media In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable Extinguishing Media Do not use water jet.

5.2 Special Hazards Arising from Substance / Mixture

Hazards from the Substance or Mixture	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous Combustion Products	Combustion products may include the following: Carbon Oxides (CO, CO2) (carbon monoxide, carbon dioxide)

5.3 Advice for Fire Fighters

Special precautions for fire-fighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for
fire-fightersFire fighters should wear appropriate protective equipment and
self-contained breathing apparatus (SCBA) with a full face-piece
operated in positive pressure mode. Clothing for firefighters
(including helmets, protective boots and gloves) conforming to
European standard EN 469 will provide a basic level of protection
for chemical incidents.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel	No action shall be taken involving any personal risk or without
	suitable training. Evacuate surrounding areas. Keep unnecessary
	and unprotected personnel from entering. Do not touch or walk
	through spilt material. Floors may be slippery; use care to avoid
	falling. Put on appropriate personal protective equipment.

For emergency responders If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

6.2Environmental Precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3Methods and Material for Containment and Cleaning Up

Small Spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large Spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, watercourses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local

6.4Reference to Other Sections

See Section 1 for emergency contact information. See Section 5 for firefighting measures. See Section 8 for information on appropriate personal protective equipment. See Section 12 for environmental precautions. See Section 13 for additional waste treatment information.

regulations. Dispose of via a licensed waste disposal contractor.



SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Protective measures Put on appropriate personal protective equipment.

Advice on general occupational Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2Conditions for Safe Storage, Including Any Incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabeled containers.

7.3Specific and End Use(s) Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure Controls / Personal Protection

8.1 Control Parameters

Occupational Exposure Limits	No exposure limit value known measures.
	Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.
Recommended Monitoring Procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be



required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level

No DNELs/DMELs available

Predicted No Effect Concentration

No PNECs available.

8.2Exposure Controls

Appropriate Engineering Controls Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organization for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Internol Enduring Performance

Respiratory Measures	Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to
	control exposure. In case of insufficient ventilation, wear
	suitable respiratory equipment. The correct choice of respiratory
	protection depends upon the chemicals being handled, the
	conditions of work and use, and the condition of the respiratory
	equipment. Safety procedures should be developed for each
	intended application. Respiratory protection equipment should
	therefore be chosen in consultation with the
	supplier/manufacturer and with a full assessment of the working
	conditions.
Fire / Calf Due to ation	conditions.
Eye / Self Protection	
	Safety glasses with side shades
	General Information:
	Because specific work environments and material handling
	practices vary, safety procedures should be developed for each
	intended application. The correct choice of protective gloves
	depends upon the chemicals being handled, and the conditions
	of work and use. Most gloves provide protection for only a
	limited time before they must be discarded and replaced (even
	the best chemically resistant gloves will break down after
	repeated chemical exposures). Gloves should be chosen in
	consultation with the supplier / manufacturer and taking
Hand Protection	account of a full assessment of the working conditions.
Hand Protection	account of a full assessment of the working conditions.
	Recommended: Nitrile Gloves
	Breakthrough time:
	Breakthrough time data are generated by glove manufacturers
	under laboratory test conditions and represent how long a glove
	can be expected to provide effective permeation resistance. It is
	important when following breakthrough time recommendations
	that actual workplace conditions are taken into account. Always
	consult with your glove supplier for up-to-date technical
	information on breakthrough times for the recommended glove
	type. Our recommendations on the selection of gloves are as
	follows:
	Continuous contact:
	Gloves with a minimum breakthrough time of 240 minutes, or
	>480 minutes if suitable gloves can be obtained. If suitable
	gloves are not available to offer that level of protection, gloves



with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes must be determined and rigorously followed.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks.

For Example:

• Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.

• Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Skin and Body:

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Refer to Standards

Respiratory protection: EN529 Gloves: EN420, EN374 Eye protection: EN166

Environmental Exposure Controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and Chemical Properties



9.1 Information on Basic Physical and Chemical Properties

Appearance	
Physical State	Semi solid
Color	Black
Odour	Not Available
Odour threshold	Not Available
рН	Not Available
Worked penetration @ 25°C	355-385
Initial boiling point and boiling range	eNot Available
Dropping point	Not Available
Flash point	Not Available
Evaporation rate	Not Available
Flammability (solid, gas)	Not Available
Upper/lower flammability or	Not Available
explosive limits	
Vapor pressure	Not Available
Vapor density	Not Available
Relative density	Not Available
SP. Gravity @15°C/ 60°F	Not Available
Solubility	Insoluble in water.
Partition coefficient:	Not Available
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
Viscosity	Not Available
Explosive properties	Not Available
Oxidizing properties	Not Available

9.20ther Information

No Additional Information

SECTION 10: Stability and Reactivity

10.1 Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

10.2 Chemical Stability



This product is stable.

10.3 Possibility of Hazardous Reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

10.4 Conditions to Avoid

Avoid all possible sources of ignition (spark or flame).

10.5 Incompatible Materials

Reactive or incompatible with Oxidizing Materials

10.6 Hazardous Decomposition Products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

11.2 Information on Toxicological Effects

Acute Toxicity Estimates	Route	ATE Value
Petroleum derived calcium salt	Oral	> 5000mg/kg
61789-86-4	Dermal	> 4000 mg/kg
	Inhalation (dusts and mists)	418.6 mg/l

Information on the likely routes of Routes of entry anticipated: Dermal, Inhalation. exposure

Potential Acute Health Effects	
Inhalation	Exposure to decomposition products may cause a health hazard.
	Serious effects may be delayed following exposure.
Ingestion	No known significant effects or critical hazards.



Skin Contact	Defatting to the skin. May cause skin dryness and irritation.
Eye Contact	No known significant effects or critical hazards.
Symptoms related to the physical, chemical and toxicological characteristics	
Inhalation	No specific data
Ingestion	No specific data
Skin Contact	Adverse symptoms may include irritation, dryness, cracking
Eye Contact	No specific data

Delayed and immediate effects and Over exposure to the inhalation of airborne droplets or aerosols also chronic effects from short and may cause irritation of the respiratory tract. long term exposure

Inhalation/Ingestion Skin Contact	Ingestion of large quantities may cause nausea and diarrhea. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Potential Chronic Health Effects	Potential risk of transient stinging or redness if accidental eye contact occurs.
Carcinogenicity	No know significant effects or critical hazards.
Mutagenicity	No know significant effects or critical hazards.
Developmental Effects	No know significant effects or critical hazards.
Fertility Effects	No know significant effects or critical hazards.

SECTION 12: Ecological Information



12.1 Toxicity

Environmental Hazard

Not classified as dangerous.

12.2 **Persistence and Degradability**

Partially biodegradable.

12.3 Bio Accumulative Potential

This product is not expected to bio accumulate through food chains in the environment.

12.4 Mobility in Soil

Soil / Water partition coefficient	Not available							
(KOC)								
	Spillages	may	penetrate	the	soil	causing	ground	water
Mobility	contamina	ation						

12.5 Result of PBT and vPVB Assessment

- PBT Not applicable
- vPVB Not applicable

12.6 Other Adverse Effects

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

SECTION 13: Disposal Considerations

13.1 Waste Treatment Methods



Methods of Disposal	Where possible, arrange for product to be recycled. Dispose of via an authorized person/ licensed waste disposal contractor in accordance with local regulations.		
	Waste Code	Waste Designation	
	13 02 08*	Other engine, gear, and lubricating oils	
		ntended use and/or the presence	
	of an potential contaminants may require an alternative waste disposal code to be assigned by the end user.		
Packing			
Methods of Disposal		product to be recycled. Dispose of nsed waste disposal contractor in ons.	
Special Precautions	way. Empty containers or l	er must be disposed of in a safe iners may retain some product ilt material and runoff and contact d sewers.	

SECTION 14: Transport Information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN Number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 UN Proper Shipping Name	-	-	-	-
14.3 Transport Hazard Class	-	-	-	-
14.4 Packing Group	-	-	-	-
14.5 Environmental Hazards	No	No	No	No
Additional Information	-	-	-	-
14.6 Special Precautions for User	Not available			

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture



EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorization None of the components are listed

Substances of very high concernNot applicableAnnex XVII - Restrictions on the manufacturer,
placing on the market and use of certain dangeroussubstances, mixtures and articles.

Other Regulations The company, as identified in Section 1, **REACH Status** sells this product in the EU in compliance with the current requirements of REACH. United States Inventory (TSCA 8b) Australia Inventory (AICS) All components are listed or exempted. Canada Inventory At least one component is not listed. China Inventory (IECSC) At least one component is not listed. Japan Inventory (ENCS) At least one component is not listed. Korea Inventory (KECI) At least one component is not listed. Philippines Inventory (PICCS) At least one component is not listed. At least one component is not listed.

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other Information

Abbreviations and Acronyms	ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by
	Road
	ATE = Acute Toxicity Estimate
	BCF = Bio Concentration Factor
	CAS = Chemical Abstracts Service
	CLP = Classification, Labeling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	CSA = Chemical Safety Assessment
	CSR = Chemical Safety Report
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	DPD = Dangerous Preparations Directive [1999/45/EC]
	DSD = Dangerous Substances Directive [67/548/EEC]



EINECS = European Inventory of Existing Commercial chemical Substances ES = Exposure Scenario EUH statement = CLP-specific Hazard statement EWC = European Waste Catalogue GHS = Globally Harmonized System of Classification and Labeling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OECD = Organization for Economic Co-operation and Development PBT = Persistent, Bio Accumulative and Toxic PNEC = Predicted No Effect Concentration RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SADT = Self-Accelerating Decomposition Temperature SVHC = Substances of Very High Concern STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure TWA = Time weighted average UN = United Nations UVCB = Complex hydrocarbon substance VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bio Accumulative

Full text of abbreviated H	H 304	May be fatal if swallowed and
statements		enters airways.
	H 413	May cause long lasting
Full text of classifications		harmful effects to aquatic life.
[CLP/GHS]	Aquatic Chronic 4, H413	LONG-TERM AQUATIC HAZARD
	Asp. Tox. 1, H304	- Category 4
		ASPIRATION HAZARD -
		Category 1

 Full text of abbreviated R Phrases
 R53- May cause long-term adverse effects in the aquatic environment.

 Full text of classifications
 Not Applicable

 [DSD/DPD]
 Not Applicable

 History
 01/12/2021

 Date of Issue
 01/01/2025

 Date of Revision
 Rexol FZC

Notice to Reader:

Prepared by

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet. The data and advice given apply when the product is sold for the stated application or applications. You should not use



the product other than for the stated application or applications without seeking advice from Rexol FZC. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Rexol FZC shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the Rexol FZC to ensure that this document is the most current available. Alteration of this document is strictly prohibited.