



T-REX CHF

PRODUCT DESCRIPTION:

T-REX CHF is a high-performance synthetic hydraulic fluid featuring ashless additives for superior efficiency. Specially formulated for modern vehicles, it is ideal for use in power steering, braking, suspension leveling, and hydraulic suspension systems. Additionally, it is suitable for shock absorbers, hydro-pneumatic suspension, and traction and stability control systems, making it a versatile and reliable multi-purpose solution.

APPLICATION:

T-REX CHF is highly recommended for the power steering and suspension systems of late model European prestige vehicles as a service refill or top-up fluid. It can serve as a direct replacement for OEM LDS fluids and Pentosin T-REX CHF 11S, reducing workshop inventory. Additionally, it can be used in certain brake systems, but it is important to consult the vehicle handbook for compatibility before use.

FEATURES & BENEFITS

- Good flow rates of fluid at extremes of temperature
- Excellent lubricating properties
- High thermal stability
- Excellent protection against wear & corrosion
- Excellent compatibility with all kind of seals and hoses

TYPICAL PROPERTIES:

P ARAMETERS	T-REX CHF (Typical Specification)
MAN	M3289
MB	345.0
PENTOSIN	CHF 11S
Chrysler	MS-11655
FORD	M2C204-A
BMW	81 22 9 407 758
VW/SEAT/SKODA/AUDI	G 002 000 (TL 521 46), G 004 000
HYUNDAI/KIA	PSF-3/PSF-4
FIAT	9.55550-AG2/9.55550-AG3 VG 22
GM	89021185/ 89021186/ 1052884/ 993294
VOLVO	1161529

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internal reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internal.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.