



T-REX POWER STEERING FLUID

PRODUCT DESCRIPTION:

T-REX POWER STEERING FLUID is a high-performance, fully synthetic oil specifically formulated for power steering and suspension systems. It features a unique blend of anti-shudder additives, dispersants, and seal swell agents, combined with a specialized synthetic base oil. This advanced formulation ensures superior wear protection, extended service life, and reduced viscosity loss.

APPLICATION:

T-REX POWER STEERING FLUID is specifically designed and highly recommended for power steering systems in all Honda vehicles, as well as Rover models 416i, 825, and 827 equipped with Honda power steering components. Additionally, it is suitable for high-performance applications in vehicles such as the Ford Tickford series, AU, BA & BF XR, FPV, and Territory SX-SY series. Its synthetic base oils and higher viscosity provide enhanced protection by reducing pump wear and maintaining optimal steering feel, even under increased heat and load conditions.

FEATURES & BENEFITS:

- Correct viscosity for Honda Power Steering units
- Compatible with OEM fluid
- Reduces power steering shudder (noise & chatter)
- Extends seal and hose life
- Multiple use power steering & suspension
- Long Service life
- Protects against rust and corrosion

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- Ford M2C134-C
- Ford M2C134-D
- Honda PSF-II
- Honda PSF-S
- Honda PSF-V

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	T-REX POWER STEERING FLUID
KV@ 104°F /40°C	D7042	cSt	TBR
KV @ 212°F /100°C	D7042	cSt	11.7
Viscosity Index	D2270	-	140
Density@15°C	D4052	g/cm ³	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internalol reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internalol.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.